

Attractive lady seeks new master

Unique crane offer

The Gottwald HMK 360 E mobile harbour crane at the Port of Copenhagen is affectionately called 'Myrna'. Having served the Port faithfully since 1990, and still very much alive and kicking, Myrna has regrettably become surplus to requirements and is now offered for sale.

CAPACITY RANGE

120 tons - 23 m radius to
43 tons - 47 m radius

If you are interested,
please contact Port-Trade's
Managing Director John Muller.

*Is Myrna too big?
Please let us know what
capacity would suit you.*



PORT-TRADE
cargo handling systems

Tel.: +45 7628 0102

www.port-trade.com

**GOTTWALD HMK 360 E
Mobile Harbour Crane**



Built 1990
Running hours approx. 12,250
Previous owners one

Work history general cargo
containers
no grabbing

Condition very good
refurbished jib
new hoist ropes
overhauled carrier (tyres 25%)

Specification

Jib length 47 m
Propping base 16.8 m x 12.5 m
Propping plates 4 pcs. 1.2 m x 6.0 m
Total number axles 8
Steerable axles 8
Driven axles 3
Tyres 32-fold, 14.00-24.32 ply
Driver's eyelevel approx. 22 m
Outreach 15 m to 47.5 m
Total weight 420 tonnes
Max. corner load 233 tonnes
Diesel engine GM 16V92T1
630 kW
Fuel tank approx. 10,000 ltrs
Running hours on tank more than 200 hrs

Operating speeds

Hoisting 120 t up to 12.5 m/m
110 t up to 15.0 m/m
40 t up to 40 m/m
18 t up to 80 m/m
Slewing up to 1.35 rpm
Luffing up to 60 m/m
Travelling up to 80 m/m

Equipment included

Automatic spreader Bromma EH5 – 40 t
Rotatable hook Bromma EH3 – 120 t
Motorgrab controls max 45 kW (no grab included)
Mains power connection option 7 kV reel with 200 m cable

PRICE ON APPLICATION

Availability: immediately

Lifting Capacities - HMK 360 E

Radius	Heavy Lift	General Cargo	Grab Capacity
	on hook	on hook	on hook
	B2	B4	B5
[m]	[t]	[t]	[t]
12	120.0	43.0	32.0
13	120.0	43.0	32.0
14	120.0	43.0	32.0
15	120.0	43.0	32.0
16	120.0	43.0	32.0
17	120.0	43.0	32.0
18	120.0	43.0	32.0
19	120.0	43.0	32.0
20	120.0	43.0	32.0
21	120.0	43.0	32.0
22	120.0	43.0	32.0
23	120.0	43.0	32.0
24	118.0	43.0	32.0
25	110.0	43.0	32.0
26	104.0	43.0	32.0
27	98.0	43.0	32.0
28	93.0	43.0	32.0
29	88.5	43.0	32.0
30	84.0	43.0	32.0
31	80.0	43.0	32.0
32	77.0	43.0	32.0
33	73.5	43.0	31.5
34	70.0	43.0	31.0
35	67.5	43.0	30.5
36	64.5	43.0	30.0
37	62.0	43.0	29.6
38	60.0	43.0	29.2
39	57.5	43.0	28.8
40	55.5	43.0	28.4
41	53.5	43.0	28.0
42	51.5	43.0	27.6
43	50.0	43.0	27.2
44	48.5	43.0	26.8
45	47.0	43.0	26.4
46	45.0	43.0	26.0
47	44.0	43.0	25.5
47.5	43.0	43.0	25.0

