

USED EQUIPMENT FOR SALE

B&W Mobile Shiploader



Figur 1 - Summer 2006



Figur 2 – Summer 2010



USED EQUIPMENT FOR SALE

B&W Mobile Shiploader

Built 2006

Running hours

Previous owners one

Work history Fiskefjord, Greenland

olivine density 2 t/m³

P.O.A.

Condition good operational

Specifications

Maximum shiploading capacity at material density approx. 2 t/m³ 2.000 tph

Average capacity estimate 1.350 tph

Samson 1600 towable reception unit, suitable for front end loaders from 3 sides

entry width 4,5 m belt width 2600 mm

conveying centres 10,3 m

holding capacity approx. 30 m³ hydraulic drive slaved ship loading conveyor dieselgenerator

Mobile ship loading conveyor, with in-line tandem fixed wheels for tow travel

length c/c 45 m

beltwidth 1200 mm belt type 25 mm, chevron cleated

belt speed variable to 2,5 m/sec variable inclination 15° to 30°

discharge remote controlled 360° radial trimming chute hydraulic drive powered from 250kW dieselgenerator on chassis max. vessel width beam 32 m

max. freeboard height 12 m

PRICE as is, ex site Aalborg

Packed in 6 pcs. 40' containers + 6pcs. 40'OTcontainers

Availability: Autumn 2010

Upon request, Port-Trade ApS can support the buyer with regard to transportation, erection and commissioning of the offered equipment.

Technical specifications are subject to confirmation